

Adventurer Tour tire specifications table

Tire Size	Service Description	UTQG	Load Range	Sidewall	Approved Rim Width	Measured Rim Width	Section Width	Overall Diameter	Tire Weight	Max Load	Tread Depth
195/65R15	91H	640 A A	STD	BLK	5.5 - 7	6	7.9	25	20	1356	10.5
205/70R16	97T	780 A A	STD	BLK	5 - 7	6	8.2	27.32	22	1609	11.5
205/65R16	95H	640 A A	STD	BLK	5.5 - 7.5	6	8.2	26.46	22	1521	10.5
215/65R16	98T	780 A A	STD	BLK	6 - 7.5	6.5	8.7	27.01	23	1653	11.5
205/60R16	92V	640 A A	STD	BLK	5.5 - 7.5	6	8.2	25.67	21	1389	10.5
215/60R16	95V	640 A A	STD	BLK	6 - 7.5	6.5	8.7	26.14	22	1521	10.5
225/60R16	98H	640 A A	STD	BLK	6 - 8	6.5	9	26.61	23	1653	10.5
205/55R16	91V	640 A A	STD	BLK	5.5 - 7.5	6.5	8.4	24.88	23	1356	10.5
225/65R17	102H	640 A A	STD	BLK	6 - 8	6.5	9	28.5	27	1874	10.5
235/65R17	104H	640 A A	STD	BLK	6.5 - 8.5	7	9.4	29.06	28	1984	10.5
225/60R17	99V	640 A A	STD	BLK	6 - 8	6.5	9	27.64	25	1709	10.5
215/55R17	94V	640 A A	STD	BLK	6 - 7.5	7	8.9	26.3	23	1477	10.5
225/55R17	97V	640 A A	STD	BLK	6 - 8	7	9.2	26.77	24	1609	10.5
215/50R17	95V	640 A A	XL	BLK	6 - 7.5	7	8.9	25.51	26	1521	10.5
225/50R17	94V	640 A A	STD	BLK	6 - 8	7	9.2	25.91	23	1477	10.5
225/45R17	91H	640 A A	STD	BLK	7 - 8.5	7.5	8.9	24.96	24	1356	10.5
235/55R18	104V	640 A A	XL	BLK	6.5 - 8.5	7.5	9.6	28.15	29	1984	10.5
235/50R18	97W	500 A A	STD	BLK	6.5 - 8.5	7.5	9.6	27.28	29	1609	10.5
235/45R18	94V	640 A A	STD	BLK	7.5 - 9	8	9.3	26.34	27	1477	10.5
235/40R19	96V	640 A A	XL	BLK	8 - 9.5	8.5	9.5	26.42	26	1565	10.5
255/50R20	109V	640 A A	XL	BLK	7 - 9	8	10.4	30.08	33	2271	10.5
195/65R15	91H	640 A A	STD	BLK	5.5 - 7	6	7.9	25	20	1356	10.5

205/70R16	97T	780 A A	STD	BLK	5 - 7	6	8.2	27.32	22	1609	11.5
205/65R16	95H	640 A A	STD	BLK	5.5 - 7.5	6	8.2	26.46	22	1521	10.5
215/65R16	98T	780 A A	STD	BLK	6 - 7.5	6.5	8.7	27.01	23	1653	11.5
205/60R16	92V	640 A A	STD	BLK	5.5 - 7.5	6	8.2	25.67	21	1389	10.5
215/60R16	95V	640 A A	STD	BLK	6 - 7.5	6.5	8.7	26.14	22	1521	10.5
225/60R16	98H	640 A A	STD	BLK	6 - 8	6.5	9	26.61	23	1653	10.5
