

# Cobra Radial G/T tire specifications table

Tire Size	Service Description	UTQG	Load Range	Sidewall	Approved Rim Width	Measured Rim Width	Section Width	Overall Diameter	Tire Weight	Max Load	Tread Depth
P215/70R14	96T	440 A B	STD	RWL	5.5 - 7	6.5	8.7	25.75	22	1554	10.5
P225/70R14	98T	440 A B	STD	RWL	6 - 7.5	6.5	8.9	26.26	24	1675	10.5
P235/60R14	96T	440 A B	STD	RWL	6.5 - 8.5	7	9.1	25.08	23	1565	10.5
P215/70R15	97T	440 A B	STD	RWL	5.5 - 7	6.5	8.7	26.69	23	1620	10.5
P225/70R15	100T	440 A B	STD	RWL	6 - 7.5	6.5	9.1	27.36	27	1753	10.5
P235/70R15	102T	440 A B	STD	RWL	6 - 8	7	9.4	27.91	28	1896	10.5
P255/70R15	108T	440 A B	STD	RWL	6.5 - 8.5	7.5	10.4	28.94	32	2183	10.5
P215/65R15	95T	440 A B	STD	RWL	6 - 7.5	6.5	8.4	25.98	22	1510	10.5
P235/60R15	98T	440 A B	STD	RWL	6.5 - 8.5	7	9.1	26.1	25	1642	10.5
P245/60R15	100T	440 A B	STD	RWL	7 - 8.5	7	9.5	26.54	27	1753	10.5
P255/60R15	102T	440 A B	STD	RWL	7 - 9	7.5	10.2	27.01	28	1885	10.5
P275/60R15	107T	440 A B	STD	RWL	7.5 - 9.5	8	10.7	28.07	31	2149	10.5
P295/50R15	105S	440 A C	STD	RWL	8 - 10	9.5	12.2	26.81	32	2061	10.5