

Cooper Commuter tire specifications table

Tire Size	Service Description	UTQG	Load Range	Sidewall	Approved Rim Width	Measured Rim Width	Section Width	Overall Diameter	Tire Weight	Max Load	Tread Depth
195/65R15	91H	580 A A	STD	BLK	5.5 - 7	6	7.9	25	18	1356	9.5
205/65R15	94H	580 A A	STD	BLK	5.5 - 7.5	6	8.2	25.47	20	1477	9.5
205/65R16	95H	580 A A	STD	BLK	5.5 - 7.5	6	8.2	26.46	21	1521	9.5
225/65R16	100T	600 A B	STD	BLK	6 - 8	6.5	9	27.48	24	1764	9.5
235/65R16	103T	600 A B	STD	BLK	6.5 - 8.5	7	9.4	28.03	25	1929	9.5
205/60R16	92H	580 A A	STD	BLK	5.5 - 7.5	6	8.2	25.67	20	1389	9.5
215/60R16	95V	580 A A	STD	BLK	6 - 7.5	6.5	8.7	26.14	21	1521	9.5
215/60R16	95T	600 A B	STD	BLK	6 - 7.5	6.5	8.7	26.14	20	1521	9.5
225/60R16	98H	580 A A	STD	BLK	6 - 8	6.5	9	26.61	22	1653	9.5
205/55R16	94H	580 A A	XL	BLK	5.5 - 7.5	6.5	8.4	24.88	20	1477	9.5
225/65R17	102T	600 A B	STD	BLK	6 - 8	6.5	9	28.5	24	1874	9.5
235/65R17	104T	600 A B	STD	BLK	6.5 - 8.5	7	9.4	29.06	26	1984	9.5
215/55R17	94V	580 A A	STD	BLK	6 - 7.5	7	8.9	26.3	22	1477	9.5
225/55R17	97V	580 A A	STD	BLK	6 - 8	7	9.2	26.77	27	1609	9.5
215/50R17	95V	580 A A	XL	BLK	6 - 7.5	7	8.9	25.51	24	1521	9.5
225/50R17	94V	580 A A	STD	BLK	6 - 8	7	9.2	25.91	22	1477	9.5
225/60R18	100H	580 A A	STD	BLK	6 - 8	6.5	9	28.62	27	1764	9.5
225/55R18	98H	580 A A	STD	BLK	6 - 8	7	9.1	27.76	27	1653	9.5
235/55R18	100V	580 A A	STD	BLK	6.5 - 8.5	7.5	9.6	28.15	27	1764	9.5