

# Discoverer ATP II tire specifications table

Tire Size	Service Description	UTQG	Load Range	Sidewall	Approved Rim Width	Measured Rim Width	Section Width	Overall Diameter	Tire Weight	Max Load	Tread Depth
265/70R16	112T	600 A B	STD	RWL	7 - 9	8	10.4	30.63	19	2469	13
265/65R17	112T	600 A B	STD	RWL	7.5 - 9.5	8	10.6	30.79	18	2469	12
275/65R18	116T	600 A B	STD	RWL	7.5 - 9.5	8	10.9	32.2	21	2756	12
275/60R20	115T	600 A B	STD	RWL	7.5 - 9.5	8	10.9	33.07	21	2679	12
LT265/75R16	123\120R	NULL	E	RWL	7 - 8	7.5	10.6	31.46	23	3415	16
LT285/75R16	126\123R	NULL	E	RWL	7.5 - 9	8	11.6	32.64	25	3750	16.5
LT245/75R17	121\118S	NULL	E	RWL	6.5 - 7.5	7	10	31.69	22	3195	16
LT265/70R17	121\118S	NULL	E	RWL	7 - 8.5	8	10.8	31.65	23	3195	16
LT285/70R17	121\118S	NULL	E	RWL	7.5 - 9	8.5	11.4	32.83	26	3195	16.5
LT275/70R18	125\122S	NULL	E	RWL	7 - 8.5	8	11.1	33.46	26	3640	16
LT275/65R18	123\120S	NULL	E	RWL	7.5 - 9	8	10.9	32.36	25	3415	16
LT275/65R20	126\123S	NULL	E	RWL	7.5 - 9.5	8	11.1	34.21	28	3750	16